




VIBXPERT® – the new two channel FFT data collector and signal analyzer for hazardous areas

for monitoring and diagnosing machine conditions in the chemical industry, in refineries, in the oil and gas industry and in any other potentially explosive environment that requires intrinsically safe measuring systems.

- ▶ Knowledge-based setups
- ▶ 102,400 lines of resolution
- ▶ Simple joystick operation
- ▶ Acceptance measurements
- ▶ Runup / coastdown analysis
- ▶ Time waveform analysis
- ▶ Balancing, 1 plane or 2 planes
- ▶ Intrinsic safety  II 2 G EEx ib IIC T4

VIBXPERT® Ex – Technical data

Measurement channels

2 analog channels (A & B), selectable:

- Voltage (AC/DC, ± 30 V max.)
- Current (AC/DC, ± 30 mA max.)
- ICP® signal (2 mA, 24 V max.)
- LineDrive signal (10 V, 10 mA max.)
- PT100 (four & two wire)
- Strain gages (full & half bridge, 5mA)

1 analog channel: temperature measurement sensor (NiCrNi)

1 digital channel: 1+1 pulse/tacho (RPM, trigger, key phaser).
Pulse & AC signals (± 26 V)

Parameters - analog measurement channels (A & B)

Frequency range	0.5 Hz to 40 kHz
Dynamic (measured/total)	96 dB / 136 dB
Sampling rate	≤ 131 kHz per channel

Outputs

Stroboscope control: TTL

Signal out: for headphone and signal processing

Memory

RAM, internal	64 MB
CompactFlash	1 GB

Display

LCD, illuminated, 480x320 pixels (1/2 VGA)

Measurement range / accuracy

RPM	10...200 000 rpm / $\pm 1\%$ / ± 1 rpm
Temperature	-50...+1000°C (NiCrNi) / $\pm 1\%$ / $\pm 1^\circ\text{C}$
Displacement*	6000 μm (p-p) / $\pm 1\%$
Velocity*	6000 mm/s (p-p) / $\pm 1\%$
Acceleration*	6000 m/s ² (p-p) / $\pm 1\%$

FFT

F _{min}	0.5 Hz ... 10 Hz, selectable
F _{max}	200 Hz ... 51.2 kHz, selectable
Lines	100 ... 102400
Window	Rectangular, Hanning, Flattop, Hamming, Blackman, Bartlett, Kaiser

Operating modes

Multimode (non-route)

- Overall values: vibration (acceleration, velocity, displacement), current, voltage (AC/DC), shock pulse (roller bearing condition), temperature, RPM
- Signals: spectrum (amplitude, envelope), time waveform, cepstrum, phase & cross-channel phase, orbit, coastdown measurement, impact test

Data acquisition (Route)

- Guidance via tree, list view or machine graphic
- Process optimization for quick data acquisition

Balancing (optional)

- Dynamic balancing in 1 or 2 planes



Supply

Lithium-ion battery	(7.2V / 4.8Ah).
Chargeable in device	charge time < 5 hours

Temperature range

Storage	-20°C .. +60°C
Operation	-10°C .. +60°C
Charge	0°C .. +50°C

Protection class

IP65, dustproof and waterproof

Intrinsic safety, classification

Ex II 2 G EEx ib IIC T4

Dimensions

250 x 220 x 37 mm (LxWxH)

Weight

1.9 kg

Vibration transducers (accessories)

VIBCODE®

Hand-held transducer with automatic location identification

- reliable identification of the coded measurement location
- reproducible measurement conditions
- intrinsic safety: Ex II 2 G EEx ib IIC T4
- order no. VIB 8.660-XVS

Industrial accelerometer - type VIB 6.142 REX

Mobile industrial accelerometer for standard machines

- machine vibration & roller bearing condition (shock pulse)
- medium and high rotational speed (> 600 rpm)
- magnetic, bonded or threaded mounting
- intrinsic safety: Ex II 2 G EEx ib IIC T4

Industrial accelerometer - type VIB 6.147 EX

Mobile industrial accelerometer for 'low-speed' machines

- machine vibration
- low rotational speed (> 120 rpm)
- magnetic, bonded or threaded mounting
- intrinsic safety: Ex II 2 G EEx ib IIC T4



Additional information is available in the six-page VIBXPERT® brochure or in the VIBXPERT® product catalog. You can download these documents directly from our website or order a printed copy by phone.

Visit us at www.pruftechnik.com

Printed in Germany VIB 9.824.07.07.G
VIBXPERT® and VIBCODE® are registered trademarks of PRÜFTECHNIK Dieter Busch AG. No copying or reproduction of this information, in any form whatsoever, may be undertaken without express written permission of PRÜFTECHNIK AG. The information contained in this leaflet is subject to change without further notice due to the PRÜFTECHNIK policy of continuous product development. PRÜFTECHNIK products are the subject of patents granted or pending throughout the world.
© Copyright 2007 by PRÜFTECHNIK AG.

PRÜFTECHNIK
Condition Monitoring
85737 Ismaning, Germany
www.pruftechnik.com
Phone: +49 89 99616-0
Fax: +49 89 99616-300
eMail: info@pruftechnik.com

Productive maintenance technology